


Mono PERC 166mm 120 Cells


# MS(360-380)MB-60H Transparent Bifacial

360/365/370/375/380 WP




## High customer value

- Lower LCOE (Levelized Cost Of Energy), reduced BOS (Balance Of System) cost, shorter payback time
- Lower guaranteed first year and annual degradation
- Designed for compatibility with existing mainstream system components
- Higher return on Investment




## High energy yield

- Excellent IAM (Incident Angle Modifier) and low irradiation performance, validated by 3rd party certifications
- The unique design provides optimized energy production under inter-row shading conditions



## High reliability

- Minimized micro-cracks with innovative non-destructive cutting technology
- Ensured PID resistance through cell process and module material control
- Resistant to harsh environments such as salt, ammonia, sand, high temperature and high humidity areas
- Mechanical performance up to 5400 Pa positive load and 2400 Pa negative load
- Class-C fire safety test passed




## High power up to 380W

- Large area cells based on 166mm silicon wafers and 1/2-cut cell technology
- Up to 20.54% module efficiency with high density interconnect technology
- Multi-busbar technology for better light trapping effect lower series resistance and improved current collection

## APPLICATIONS >>



On-grid residential  
roof-tops



On-grid commercial/  
industrial roof-tops




MAXIMUM EFFICIENCY


20.54%

POSITIVE POWER  
TOLERANCE


0 ~ +5W




### DIMENSIONS OF PV MODULE(mm)




Front View




Back View



### I-V CURVES OF PV MODULE(370W)



### P-V CURVES OF PV MODULE(370W)



### ELECTRICAL DATA (STC)

Parameter	360	365	370	375	380
Peak Power Watts- $P_{MAX}$ (Wp)*	360	365	370	375	380
Power Tolerance- $P_{MAX}$ (W)	0 ~ +5				
Maximum Power Voltage- $V_{MPP}$ (V)	33.6	33.9	34.2	34.4	34.7
Maximum Power Current- $I_{MPP}$ (A)	10.70	10.76	10.82	10.89	10.96
Open Circuit Voltage- $V_{OC}$ (V)	40.7	41.0	41.3	41.6	41.9
Short Circuit Current- $I_{SC}$ (A)	11.24	11.30	11.37	11.45	11.52
Module Efficiency $\eta_m$ (%)	19.46	19.73	20.0	20.27	20.54

STC: Irradiance 1000W/m<sup>2</sup>, Cell Temperature 25°C,  
Air Mass AM1.5. \*Measuring tolerance: ±3%.

### ELECTRICAL DATA (NOCT)

Parameter	271	275	279	283	287
Maximum Power- $P_{MAX}$ (Wp)	271	275	279	283	287
Maximum Power Voltage- $V_{MPP}$ (V)	31.5	31.8	32.0	32.2	32.5
Maximum Power Current- $I_{MPP}$ (A)	8.60	8.65	8.71	8.77	8.83
Open Circuit Voltage- $V_{OC}$ (V)	38.3	38.6	38.9	39.2	39.4
Short Circuit Current- $I_{SC}$ (A)	9.06	9.10	9.16	9.23	9.28

NOCT: Irradiance at 800W/m<sup>2</sup>, Ambient Temperature 20°C, Wind Speed 1m/s.

### MECHANICAL DATA

Solar Cells	Monocrystalline
Cell Orientation	120 cells
Module Dimensions	1765×1048×30 mm (69.49×41.25×1.18 inches)
Weight	20 kg
Glass	3.2 mm (0.13 inches), High Transmission, AR Coated Heat Strengthened Glass
Encapsulant Material	EVA
Backsheet	Transparent
Frame	30 mm(1.18 inches) White, anodized aluminium alloy
J-Box	IP 68 rated (3 bypass diodes)
Cables	Photovoltaic Technology Cable 4.0mm <sup>2</sup> (0.006 inches <sup>2</sup> ) Portrait: N 300mm/P 300mm(11.02/11.02 inches) Length can be customized
Connector	MC4 Compatible

\*Please refer to regional datasheet for specified connector.

### TEMPERATURE RATINGS

NOCT(Nominal Operating Cell Temperature)	43°C (±2°C)
Temperature Coefficient of $P_{MAX}$	- 0.34%/°C
Temperature Coefficient of $V_{OC}$	- 0.25%/°C
Temperature Coefficient of $I_{SC}$	0.04%/°C

### MAXIMUM RATINGS

Operational Temperature	- 40 ~ +85°C
Maximum System Voltage	1500V DC (IEC)
	1000V DC (IEC)
Max Series Fuse Rating	20A

### WARRANTY

- 15 year Product Workmanship Warranty
- 25 year Power Warranty
- 2.5% first year degradation
- 0.5% Annual Power Attenuation

\*Please refer to product warranty for details.

### PACKAGING CONFIGURATION

- Modules per pallet: 37 pieces
- Modules per 40' container: 1040 pieces



CAUTION: READ SAFETY AND INSTALLATION INSTRUCTIONS BEFORE USING THE PRODUCT.

© 2021 Maysun Solar Co.,Ltd. All rights reserved. Specifications included in this datasheet are subject to change without notice.

Website: [www.maysunsolar.com](http://www.maysunsolar.com)